DATA SHEET



RHINO ENCLOSURES

Universal Self-Locking Storage Enclosure Series



Rhino Series enclosures support remote deployment of network electronics, power supplies and RF components at broadband node locations. They also facilitate the management and storage of fiber optic, coaxial, and copper cables. Flexible and modular in design, Rhino enclosures permit unique, customerspecified features to be included quickly and cost effectively.

Combined with Channell's full line of active and passive electronic equipment enclosures, a complete system can be designed that supports the requirements of broadband telecommunications network operators. Constructed of heavy gauge mill galvanized steel, Rhino enclosures and hardware resist corrosion, protect equipment, and provide security. Multiple power access and electrical options include a commercial power entrance, wiring harness, and surge protection. Mounting pads and vaults are also available. A pole mount version of the Rhino Series is also available for power supply locations.

Looking for a Fiber Hub? Check out our Optimus Cabinets in our Fiber Optic Division: FiberX.

FEATURES

- Self-locking cover lenses with multiple security lock options
- Coated with Bellcore compliant polyester powder paint
- Available with closed-back or open-back chassis frame designs
- Top entry cover lens facilitates post wire applications
- Closed-back boxes have rear and bottom cable entry knockouts
- Adjustable tap mounting plate
- Optional demarcation plate kits available with or without F-81 barrel splices installed

PART NUMBER MATRIX

		RXXXX	P	CX	BO	FO	PX	TX	LX	EX	EOX	CX	COX
Rhino Ca	abinet Si	iize											
Applicati													
	Р	PSS-Power Supply/Batteries											
Color													
	C1	Light Green											
	C2 C3	Beige Dark Green											
	C3 C4	Gray											
		vice Entrance)											
-		-											
	PH PJ	External Breaker Box 120/15 & Duplex C External Breaker Box 120/20 & Duplex (15A 20 A									
	PK	External Breaker Box 120/20 & Duplex (External Breaker Box 240/15 & Duplex (
Harness			outiet	15/4									
	тк	3 Battery Harness Alpha plus 2 BSSO											
	TN	3 Battery Harness Alpha plus 1 BSSO											
	TR	3 Battery Harness Alpha plus 1 BSSO 6 Battery Harness Alpha plus 2 BSSO											
Lock													
	LB	Pattern Lock											
	LC	Pattern Lock											
	LG	Pattern Lock VL2000 Lock											
	L1 L3	Alpha Gem Lock											
	E3	s (1) A-SPI (Alpha Power Inserter)											
	E6	(1) A-SPI (Alpha Power Inserter) + A-LF	XIX (Re	d Indic	ator Ligh	+)							
	E8	(1) A-SPI (Alpha Power Inserter) + (1) A	-LRIX	(red) +	(1) A-LR	lX (gree	n) Light						
	EX1	MTS (Magnetic Tamper Switch)											
	СХ	N/A											
	C05	Vault Footing Brackets											



Where The Industry Connects.

WORLDWIDE HEADQUARTERS: Channell Commercial Corporation, Rockwall, TX, United States • Tel 800.423.1863 • Fax 951.296.2322 CANADA: Channell Canada, Inc., Mississauga, ON, Canada • Tel 905.565.1700 • Fax 905.565.8282 EUROPE, MIDDLE EAST, AFRICA: Channell Ltd., Dartford, United Kingdom • Tel 44.1322.312590 • Fax 44.1322.508490 AUSTRALIA, ASIA, PACIFIC RIM: Channell Pty. Ltd., Seven Hills, NSW, Australia • Tel 61.2.8884.4111 • Fax 61.2.8814.8841 **DEVELOPING LOCATION: Mexico City, D.F., Mexico**

www.channell.com

All specifications subject to change without notice. © 2020 Channell Commercial Corporation. All rights reserved.