GRADE LEVEL BOXES (GLB®) FOR BROADBAND AND TELECOMMUNICATIONS



ORDERING GUIDE

GREENBELT APPLICATIONS

Channell provides High Density Polyethylene (HDPE) grade level boxes and lids in a variety of depths and sizes for greenbelt applications. These boxes are designed to meet the specific fiber, coax and copper needs of the broadband, telecommunications and utilities industries. They can be used in areas of pedestrian traffic in conjunction with various Channell products in below grade applications.



GLB610 Snap-in Cover Top Diameter: 6.0" (152.4mm) Depth: 10.0" (254.0mm) Bottom Inside Diameter: 8.5" (215.9mm)



GLB912 L-Bolt Cover Top Diameter: 9.5" (241.3mm) Depth: 12.0" (304.8mm) Bottom Inside Diameter: 12.5" (317.5mm)



Top Inside Dimensions: 10.0" Width X 15.0" Length (254.0mm X 382.0mm)
Depth: 12.0" (304.8mm)
Bottom Inside Dimensions: 14.0"Width X 19.0" Length (355.6mm X 482.6mm)
(Available with 6" (152.4mm) extension)

GLB1419

L-Bolt Cover



GLB1111 L-Bolt Cover Top Inside Dimensions: 11.0" Width X 11.0" Length (279.4mm X 279.4mm) Depth: 16.0" (406.4mm)



GLB1620 L-Bolt Cover Top Inside Dimensions: 16.0" Width X 20.0" Length (406.4mm X 508.0mm) Depth: 18.0" (457.2mm)



GRADE LEVEL BOXES (GLB®) FOR WATER IRRIGATION





ORDERING GUIDE

GREENBELT APPLICATIONS

Channell provides High Density Polyethylene (HDPE) grade level boxes and lids in a variety of depths and sizes for greenbelt applications. These boxes are designed to meet the specific fiber, coax and copper needs of the broadband, telecommunications and utilities industries. They can be used in areas of pedestrian and golf buggy traffic plus maintenance vehicle traffic in conjunction with various Channell products in below grade applications. Below Grade locators keeps the play moving and enhance the aesthetics of your surroundings.



GLB610 Snap-in Cover Top Diameter: 6.0" (152.4mm) Depth: 10.0" (254.0mm) Bottom Inside Diameter: 8.5" (215.9mm)



GLB912 L-Bolt Cover Top Diameter: 9.5" (241.3mm) Depth: 12.0" (304.8mm) Bottom Inside Diameter: 12.5" (317.5mm)



Top Inside Dimensions: 10.0" Width X 15.0" Length (254.0mm X 382.0mm)
Depth: 12.0" (304.8mm)
Bottom Inside Dimensions: 14.0"Width X 19.0" Length (355.6mm X 482.6mm)
(Available with 6" (152.4mm) extension)

GLB1419

L-Bolt Cover



GLB1111 L-Bolt Cover Top Inside Dimensions: 11.0" Width X 11.0" Length (279.4mm X 279.4mm) Depth: 16.0" (406.4mm)



GLB1620 L-Bolt Cover Top Inside Dimensions: 16.0" Width X 20.0" Length (406.4mm X 508.0mm) Depth: 18.0" (457.2mm)





"L" Bolt Cover Security

Marker/Locator (A04)

ORDERING INFORMATION: GLB® FOR BROADBAND AND TELECOMMUNICATIONS

| | | | GLB | XXXX | XX | X | -1 | X | X | A0 |
|----------------|------------|----------------------------------------|------------------------------|---------------------|------|---|----|---|---|----|
| Description — | | | | | | | | | | |
| GLB | _ | Grade Level Box | | | | | | | | |
| ize ——— | | | | | | | | | | |
| 6 | _ | Round, Top Diameter 6" (152.4mm), | , Depth 10" (25 ₄ | 4.0mm) | | | | | | |
| 9 | _ | Round, Top Diameter 9.5" (241.3mm | | | | | | | | |
| 1111 | - | 11" Width x 11" Length (279.4mm x 2 | 279.4mm), Dept | th 16" (406.4mm) | | | | | | |
| 1419 | - | 10" Width x 15" Length (335.0mm x | 382.0mm), De | pth 12" (304.8mm) | | | | | | |
| 1620 | - | 16" Width x 20" Length (406.4mm x | x 508.0mm), D | epth 18" (457.2mm) | | | | | | |
| ody Depth – | | | | • | | | | | | |
| 10 | - | 10" (254.0mm), GLB610 only | | | | | | | | |
| 12 | - | 12" (304.8mm), GLB912, and GLB14 | 419 only | | | | | | | |
| 16 | _ | 16" (406.4mm), GLB1111 only | , | | | | | | | |
| 18 | _ | 18" (457.2mm), GLB1620 only | | | | | | | | |
| Cover Color – | | . , | | | | | | | | |
| 1 | - | Green | | | | | | | | |
| 3 | _ | Gray | | | | | | | | |
| over Identifi | cation | | | | | | | | | |
| В | _ | Broadband | | | | | | | | |
| T | _ | Telecommunications | | | | | | | | |
| Ν | _ | No Logo (Blank) | | | | | | | | |
| over Type — | | | | | | | | | | |
| 1 | _ | Solid Thermoplastic | | | | | | | | |
| Cover Security | <i>,</i> — | ı | | | | | | | | |
| 0 | _ | No Bolt (GLB610 only) | | | | | | | | |
| 1 | _ | Plastic L-Bolt (Standard feature for C | GLB912, GLB111 | 1, GLB1419 and GLB1 | 620) | | | | | |
| Accessory Op | tions | | | <u> </u> | - | | | | | |
| A03 | _ | Telescoping Vertical Mounting Bracke | et (GLB1620 or | nlv) | | | | | | |
| | | Marker/Locator (installed on undersic | | 1- | | | | | | |

Example: GLB1620181B11A04 - GLB1620, 18" Depth, Green Cover, Broadband Cover Identification, Solid Thermoplastic Cover, Plastic L-Bolt, Marker/Locator



UNITED STATES: Channell Commercial Corporation, Temecula, CA, United States • Tel 800.423.1863 • Fax 951.296.2322

CANADA: Channell Canada, Inc., Mississauga, ON, Canada • Tel 905.565.1700 • Fax 905.565.8282

EUROPE, MIDDLE EAST, AFRICA: Channell Ltd., Dartford, United Kingdom • Tel 44.1322.312590 • Fax 44.1322.508490

AUSTRALIA, ASIA, PACIFIC RIM: Channell Pty. Ltd., Seven Hills, NSW, Australia • Tel 61.2.8884.4111 • Fax 61.2.8814.8841

DEVELOPING LOCATIONS: Dallas, TX, United States • Mexico City, D.F., Mexico

WORLDWIDE HEADQUARTERS: Channell Commercial Corporation • Tel 951.719.2600 • 26040 Ynez Road, P.O. Box 9022, Temecula, CA 92589-9022, United States

www.channell.com