

OCFH OPTIMUS FIBER HUB CABINETS

OCFHXXX Cross Connect Vault/Pad Mount



The Optimus Fiber Hub Cabinet is a high-density, vault-mounted fiber distribution hub solution designed for centralized split, FTTX deployment architectures. The OCFH features a robust, powder-coated aluminum shell with various sizes accommodating up to 576F in a compact footprint and allows operators to scale the cabinet to their network design maximizing return on investment.

FEATURES

- **Fiber Bend Radius Protection** provides timeless performance.
- **Intuitive fiber routing** provides ease of use and repeatable splitter installation.
- **Easy connector access** allows easy cleaning access and quick reliable connections.
- **Diverse splitter, WDM/Splitter, and CWDM module choice** allow deployment in all GPON, EPON, and RFOG deployments as well in both centralized split and decentralized split network configurations.
- **Splitter module fits all styles of Fiber Hub enclosures;** which minimizes inventory and guarantees that the technician has the right modules to complete the work order.
- **Splitter Modules include 1X32, 2x32, 1X16, 2X16, Dual 1X16, 1X8, Quad 1X8, 1X4, Sextuple 1X4, 1X2, and many versions of CWDM and DWDM multiplexer modules.**
- **Splitter Modules exceed GR-1209 and GR-1221 optical requirements and connect with GR-326 connectors** delivering superb optical performance.
- **Cabinets are Pole, Wall, and H-Frame mountable** giving them placement flexibility.
- **Cabinets are manufactured with corrosion resistant 5052 H32 high strength aluminum with welded seams and a powder coated finish** will deliver decades of cabinet life.
- **Powder coated, welded and gasketed Cabinets deliver NEMA 4 water tight and dust tight performance.**

SPECIFICATIONS

Distribution Count	Dimensions	Recommended Feed Count	Splitter Module Capacity	BULK Grade Level Box Options
72,96,144	15" w X 28" h X 14" d	24 Fiber (12 and 36 optional)	8	24x36x36 / 30x48x36 / 36x60x36
288	20" w X 28" h X 14" d	24 Fiber (36F and 48F optional)	15	24x36x36 / 30x48x36 / 36x60x36
432	27" w X 36" h X 16" d	48 Fiber (24F, 36F, 48F optional)	21	30x48x36 / 36x60x36
576	27" w X 32" h X 16" d	48 Fiber (24F, 36F, 48F optional)	27	30x48x36 / 36x60x36



CHANNELL

Where The Industry Connects.

WORLDWIDE HEADQUARTERS: Channell Commercial Corporation, Rockwall, TX, United States • Tel 800.423.1863 • Fax 951.296.2322

CANADA: Channell Canada, Inc., Mississauga, ON, Canada • Tel 905.565.1700 • Fax 905.565.8282

EUROPE, MIDDLE EAST, AFRICA: Channell Ltd., Dartford, United Kingdom • Tel 44.1322.312590 • Fax 44.1322.508490

AUSTRALIA, ASIA, PACIFIC RIM: Channell Pty. Ltd., Seven Hills, NSW, Australia • Tel 61.2.8884.4111 • Fax 61.2.8814.8841

DEVELOPING LOCATION: Mexico City, D.F., Mexico

www.channell.com

All specifications subject to change without notice. © 2022 Channell Commercial Corporation. All rights reserved.