






QUICK REFERENCE CHART

PRODUCT	DIMENSIONS	SPLICE CAPACITY	FEEDER / DROP DENSITY	SC-APC ADAPTER PORT	CONFIGURATION	APPLICATION	ENVIRONMENTAL SEALING	TEST STANDARDS	GROUNDING	HARD-ENED OPTION	SPLITTERS	CABLE DIAMETER RANGE	PALLET QTY
G5NT 	Internal Diameter 5" (127mm) Height 11" (279.4mm) External Diameter 8.5" (215.9mm) Height 14" (335.6mm)	72F (single stacked) 144F (double stacked) 192F (mass fusion)	1 Main Oval Port 12 Drop Ports	16	Butt Splice	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm)	96 Single 144 Quad
G5NB 	Internal Diameter 5" (127mm) Height 11" (279.4mm) External Diameter 8.5" (215.9mm) Height 14" (335.6mm)	72F (single stacked) 144F (double stacked) 192F (mass fusion)	1 Main Oval Port 8 Drop Ports 1 Branch Port	16	Butt Splice	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm) Branch 0.4 - 0.8" (10.16 - 20.32mm)	96 Single 144 Quad
G6 	Internal Diameter 6" (152.4mm) Height 18" (457.2mm) External Diameter 9.5" (241.3mm) Height 22" (558.8mm)	96F (single stacked) 192F (double stacked)	1 Main Oval Port 16 Drop Ports 1 Ground Port	16	Butt Splice	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Optional bond strap and clips available	Yes	PLC Type 60mm x 7mm x 4mm 6 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm) Branch 0.4 - 0.8" (10.16 - 20.32mm)	30
G9 	Internal Diameter 9" (228.6mm) Height 20" (101.6mm) External Diameter 12" (304.8mm) Height 22.75" (577.85mm)	144F (single stacked) 288F (double stacked)	1 Main Oval Port 16 Drop Ports 2 Branch Ports 1 Ground Port	16	Butt Splice	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Optional bond strap and clips available	Yes		Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm) Branch 0.4 - 0.8" (10.16 - 20.32mm)	16
YELLOWJACKET 	External Width 16.0" (101.6mm) Height 8.75" (101.6mm) Depth 5.75" (101.6mm)	72F (single stacked) 144F (double stacked) 192F (mass fusion)	4 Main Cable Ports 16 Drop Ports	16	Butt Splice Aerial Terminal	Aerial Strand Pedestal	Dust Resistant Moisture Resistant	Telcordia GR771 Core IP65 IEC 61300	Yes - Optional bond strap and clips available	Yes 8 ports max	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.1 - 0.9" (2.54 - 22.86mm) Drop 0.062 - 0.19" (1.5748 - 4.826mm)	108

All specifications subject to change without notice. © 2023 Channell Commercial Corporation. All rights reserved.